

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number  
**WO 2005/009669 A1**

(51) International Patent Classification<sup>7</sup>: **B23P 15/26**

(21) International Application Number:  
PCT/SE2004/000896

(22) International Filing Date: 9 June 2004 (09.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0302127-6 24 July 2003 (24.07.2003) SE

(71) Applicant: SWEP INTERNATIONAL AB [SE/SE];  
Bävergatan 9, P.O. Box 105, S-261 22 Landskrona (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): RISSLER, Per  
[SE/SE]; De La Rose Sträte 9, S-239 30 Skanör (SE).  
NILSSON, Peter [SE/SE]; Viktoriagatan 11, S-261 35  
Landskrona (SE).

(74) Agent: LARSEN, Stig; Allégatan 28, S-234 32 Lomma  
(SE).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: A METHOD OF MANUFACTURING A PLATE HEAT EXCHANGER



(57) Abstract: In manufacturing brazed, double wall plate heat exchangers the double walls (5, 6) should comprise areas (5a, 5b) connected and sealed to each other around the port holes of the exchanger. This is obtained thereby that the said areas (5a, 5b) are shaped such as to comprise areas not covering each other. The brazing is thus established by capillary suction of brazing material from other plate areas.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*